

# MUSIC WALL MOUNT SPEAKER

pearl  
one more better



Models		HYB158-6	HYB158-5	HYB158-4	HYB158-3
Speaker type		Two-way Full range			
Peak power handling		240 W	160 W	120 W	80 W
Program power handling		120 W	80 W	60 W	40 W
RMS/AES power handling		60 W	40 W	30 W	20 W
Impedance		8 Ω	8 Ω	8 Ω	8 Ω
Sensitivity (1W/1m)		89 dB	87 dB	84 dB	81 dB
Sound Pressure (Max. W/1m)	@ 8 Ω	107 dB	103 dB	99 dB	94 dB
	@ 100 V	105 dB	102 dB	97 dB	91 dB
Frequency	Response (± 3 dB)	65 Hz - 20 kHz	85 Hz - 20 kHz	100 Hz - 20 kHz	120 Hz - 20 kHz
	Range (-10 dB)	55 Hz - 20 kHz	75 Hz - 20 kHz	85 Hz - 20 kHz	105 Hz - 20 kHz
Connectors		4-pin Press Terminal Block	4-pin Press Terminal Block	4-pin Press Terminal Block	4-pin Press Terminal Block
Drivers		1" Dome tweeter	0.5" Dome tweeter	0.5" Dome tweeter	0.5" Dome tweeter
		6.5" MF / LF Woofer	5.25" MF / LF Woofer	4" MF / LF Woofer	3" MF / LF Woofer
Line Transformer Tappings	1	122.5 Ω - 100 V / Not used - 70 V / 40 W	163 Ω - 100 V / Not used - 70 V / 30 W	250 Ω - 100 V / Not used - 70 V / 20 W	500 Ω - 100 V / Not used - 70 V / 10 W
	2	250 Ω - 100 V / 40 W - 70 V / 20 W	333 Ω - 100 V / 30 W - 70 V / 15 W	500 Ω - 100 V / 20 W - 70 V / 10 W	1000 Ω - 100 V / 10 W - 70 V / 5 W
	3	500 Ω - 100 V / 20 W - 70 V / 10 W	666 Ω - 100 V / 15 W - 70 V / 7.5 W	1000 Ω - 100 V / 10 W - 70 V / 5 W	2000 Ω - 100 V / 5 W - 70 V / 2.5 W
	4	1000 Ω - 100 V / 10 W - 70 V / 5 W	1332 Ω - 100 V / 7.5 W - 70 V / 3.75 W	2000 Ω - 100 V / 5 W - 70 V / 2.5 W	4000 Ω - 100 V / 2.5 W - 70 V / 1.25 W
Dimensions		215 x 302.9 x 189.5 mm (W x H x D)	175 x 250 x 155.8 mm (W x H x D)	140 x 200 x 135 mm (W x H x D)	106 x 150 x 114 mm (W x H x D)
Weight		2.355 kg	1.595 kg	1.246 kg	0.835 kg
Operating temperature		-20 °C ~ 60 °C			
Front finish		Aluminium grill			
Colours		Black (RAL9005) White (RAL9003)			